

## Key Features

- High performance HF compression driver and LF woofer
- Rotary dispersion horn
- Minimally sized to be visually unobtrusive
- Pole Mount Cup
- 10 eye bolt suspension points
- Quick release fly track on top and bottom
- Asymmetric enclosure provides multiple mounting angles
- Rotatable logo
- Able to be used as a stage monitor



## Specifications

The V12 is engineered to provide high definition, high output in a near field application. The V12 loudspeaker incorporates a 12" low frequency woofer and 1.77" voice coil high frequency compression driver. The woofer is mounted in a vented enclosure that is tuned for optimum low frequency response. The compression driver is mounted on a asymmetric rotatable horn with a dispersion angle of 80° and 50°.

The V12 has an asymmetric shape. It has a 45° angle for the speaker to be used as a floor monitor. It also has a 15° angle for ceiling mounting. The V12 also is equipped with a pole mount cup. The Fly track is used for a faster secure installation.

The system produces a frequency response is from 55Hz to 20KHz and is capable of producing a peak level of 126dB. The components inside the V12 are able to handle 350 watts of amplifier power and a peak power of 700 watts.

## Physical

Model	V12
System Configuration	2 way, Full Range
LF	1x 12-in
HF	1x 1-in exit 1.77-in voice coil compression driver on a Rotary Horn
Crossover	Passive
Frequency Response	70Hz-20KHz
Axial sensitivity 1w/1m	97dB
Power Rating	RMS 350W Peak 700W
Finish	Black Textured Paint
Connectors	2x NL4
Hardware	10 Threaded mounting point, Fly track, Pole mount cup
Grille	Foam backed, Black powder coated grill
Dimensions	H 24.25" L 12.25" W 15.5"
Weight	52lb